

VERECRAN 100

PRODUCT DESCRIPTION AND USES

Root-proof glass fleece manufactured by bonding of nonwoven glass fiber.
VERECRAN 100 is used as a separation layer.

COMPOSITION

Separation layer	Nonwoven glass fiber
------------------	----------------------

DIMENSIONAL CHARACTERISTICS

	50 m x 1 m	100 m x 1 m	100 m x 2 m
Nominal width (mm)	1000	1000	2000
Roll nominal length (m)	50	100	100
Mass per roll (kg)	5.6	10.6	21.2

PERFORMANCES

Test	Standard	Unit	Average value
Tensile strength	EN 29073-3	N/50 mm	≥ 300
Elongation	EN 29073-3	%	≥ 1.2

ISO 9001 REFERENCE DOCUMENT

Our products are manufactured by certified ISO 9001 plants



PACKAGING

	50 m x 1 m	100 m x 1 m	100 m x 2 m
Rolls quantity per truck pallet	23	12	14
Rolls quantity per container pallet		10	10
Rolls quantity per wooden box		10	10

COMPLEMENTARY INFORMATIONS

Values	Where 2 values for given characteristics are shown, the first is for longitudinal direction and the second is for the cross direction.
Tolerances	The average values derived from standard tests and are subject to the usual production variations. Some slight variations can be noticed as the values are based on the average values obtained from several plants.
Modification(s)	Our company reserves the right to modify its composition as a result of technologic and experiments improvements. This product data sheet supersedes the previous edition, to obtain the up-date technical data sheet, please contact our technical department
Hazardous classification	It is not classified as dangerous according to the international regulation (ADR, RID, IATA, and RTMDR)
Complementary information	This document is only a product technical data sheet, regarding each waterproofing design, please, consult the concerned technical agreement and in case of doubt contact our technical department.
Storage	This product is packaged in rolls set up vertically on pallet or wooden box. It must be stored vertically under shelter, away from heat sources.