

ASSOUR PARQUET

PRODUCT DESCRIPTION AND USES

Thin sound-deadening underlay for floating wood parquet or floating laminated flooring.

This product is used as:

- Intended for a laying under floating full-surface bonded parquets or under laminated flooring for private premises.
- On new substrates: concrete slab, dry screed, wood panels, plywood, particleboard, OSB boards ...
- On old hard flooring: stones, marble, tiling ...

Thin sound-deadening under layer to be applied below laminated floor covering, parquets ...

The application of ASSOUR PARQUET has to be in accordance with NF P 63 -204 (DTU 51.11).

COMPOSITION

Surface	Plastic film with self-adhesive selvedge
Blend	Bitumen
Under face	Glass matt fiber

DIMENSIONAL CHARACTERISTICS


Nominal thickness (mm)	3.5
Thickness dB (mm)	3.0
Nominal width (mm)	1000
Roll nominal length (m)	10.0
Area density (g/m ²)	579
Mass per roll (kg)	5.9

PERFORMANCES

Test	Standard	Unit	Average value
Dynamic stiffness	EN 29052-1	mN/m ³	6
Difference in thickness before and after compression	EN 12431	mm	1.0

- Impact noise reduction index:

ISO 9001 REFERENCE DOCUMENT

<p>Our products are manufactured by certified ISO 9001 plants</p>	
---	---

PACKAGING

Rolls quantity per truck pallet	28
Rolls quantity per container pallet	30
Rolls quantity per wooden box	

COMPLEMENTARY INFORMATIONS

Values	Where 2 values for given characteristics are shown, the first is for longitudinal direction and the second is for the cross direction.
Tolerances	The average values derived from standard tests and are subject to the usual production variations. Some slight variations can be noticed as the values are based on the average values obtained from several plants.
Modification(s)	Our company reserves the right to modify its composition as a result of technologic and experiments improvements. This product data sheet supersedes the previous edition, to obtain the up-date technical data sheet, please contact our technical department
Hazardous classification	It is not classified as dangerous according to the international regulation (ADR, RID, IATA, and RTMDR)
Complementary information	This document is only a product technical data sheet, regarding each waterproofing design, please, consult the concerned technical agreement and in case of doubt contact our technical department.
Storage	This product is packaged in rolls set up vertically on pallet or wooden box. It must be stored vertically under shelter, away from heat sources.