

COLLE PAR

PRODUCT DESCRIPTION AND USES

Colle PAR is a bitumen based thixotropic cold adhesive containing solvents.

It is used as cold adhesive glue for insulation board on bituminous waterproofing systems.
It is also used as cold adhesive glue for bitumen shingles on pitched roofs.


COMPOSITION

Colle PAR	Bitumen, additives, white spirit solvent
-----------	--

MAIN CHARACTERISTICS

Density	1.06
Dry content (%)	84
Mass per can (kg)	25

ISO 9001 REFERENCE DOCUMENT

Our products are manufactured by certified ISO 9001 plants	
--	---

PACKAGING

Cans quantity per truck pallet	24
Cans quantity per container pallet	
Cans quantity per wooden box	22

GENERALITIES ABOUT APPLICATION

Using	This product it is used to bond insulation boards over concrete or bituminous vapour barrier with sand top surface. The allowed insulation are polystyrene, perlite, mineral wool, polyurethane and PIR insulation board on built-up system waterproofing system under heavy protection.
Application	The product is applied by spots with a trowel on a clean and dry support at an average rate of 500g/m ² . It is required to apply 5 spots of glue for each panel at the angles and in the middle of the insulation board.

COMPLEMENTARY INFORMATIONS

Values	Where 2 values for given characteristics are shown, the first is for longitudinal direction and the second is for the cross direction.
Tolerances	The average values derived from standard tests and are subject to the usual production variations. Some slight variations can be noticed as the values are based on the average values obtained from several plants.
Modification(s)	Our company reserves the right to modify its composition as a result of technologic and experiments improvements. This product data sheet supersedes the previous edition, to obtain the up-date technical data sheet, please contact our technical department
Hazardous classification	It is classified as dangerous according to the international regulation (ADR, RID, IATA, and RTMDR). The Safety Data Sheet is available here: https://www.siplast.fr/profil/maitres-ouvrage-maitres-oeuvre/fds
Complementary information	This document is only a product technical data sheet, regarding each waterproofing design, please, consult the concerned technical agreement and in case of doubt contact our technical department.
Storage	This product is packaged in cans set up vertically on pallet or wooden box. It must be stored vertically under shelter, away from heat sources.