

ASSOUR 22 CONFORT

PRODUCT DESCRIPTION AND USES

Thin sound deadening underlay under floating concrete screeds, with incorporated adhesive selvedge. It reduces the impact noise transmission through the concrete deck. Assour 22 Confort is applied in accordance with French Technical standard DTU 26.2, 52.1 and NF P 61-203.

This product is classified:

- SC1 a₂ A Ch / SC₁ b₂ A Ch

COMPOSITION

Surface	Plastic film with self-adhesive selvedge
Blend	Bitumen
Under face	Glass matt fiber


DIMENSIONAL CHARACTERISTICS

Nominal thickness (mm)	3.0
Thickness dB (mm)	2.9
Nominal width (mm)	1000
Roll nominal length (m)	20.00
Area density (g/m ²)	384
Mass per roll (kg)	7.8

PERFORMANCES

Test	Standard	Unit	Average value
Impact noise reduction index, ΔL_w		dB	22
Nail tearing resistance	EN 12310-1	N	148 x 150
Dynamic stiffness	EN 29052-1	mN/m ³	7

ISO 9001 REFERENCE DOCUMENT

	 ISO 9001:2015 BUREAU VERITAS Certification
--	---

Our products are manufactured by certified ISO 9001 plants

PACKAGING

Rolls quantity per truck pallet	16
Rolls quantity per container pallet	
Rolls quantity per wooden box	

COMPLEMENTARY INFORMATIONS

Values	Where 2 values for given characteristics are shown, the first is for longitudinal direction and the second is for the cross direction.
Tolerances	The average values derived from standard tests and are subject to the usual production variations. Some slight variations can be noticed as the values are based on the average values obtained from several plants.
Modification(s)	Our company reserves the right to modify its composition as a result of technologic and experiments improvements. This product data sheet supersedes the previous edition, to obtain the up-date technical data sheet, please contact our technical department
Hazardous classification	It is not classified as dangerous according to the international regulation (ADR, RID, IATA, and RTMDR)
Complementary information	This document is only a product technical data sheet, regarding each waterproofing design, please, consult the concerned technical agreement and in case of doubt contact our technical department.
Storage	This product is packaged in rolls set up vertically on pallet or wooden box. It must be stored vertically under shelter, away from heat sources.