

## **Portoghese Flexa**

The Portoghese Flexa is a large format tile (13 pcs/m<sup>2</sup>) which fulfills the needs of the modern architecture as well as of the most traditional roofs. Quick and easy to lay with flexible overlap up to 1,5 cm.

TECHNICAL DATA	UM		
Dimension	mm	447(L) x 263(W)	
Weight	kg	3,2	
Batten gauge	mm	345 – 360	
Mechanical strength	daN	> 120	
External fire resistance		B <sub>roof</sub>	
Reaction to fire		A1	
Covering capacity	pcs/sqm	ca. 13	
Minimum pitch		30% (16,7°)	
Cover width	mm	214	
Packaging	pcs/pallet	180 (domestic pack.) 192/256 (export pack.)	







**Dimensions in millimeters** 



Monier Sr.I. via valle Pusteria 21 39030 - Chienes (BZ), Italy bmigroup.com/it

**Braas** clay roof tiles satisfy the requirements of the **UNI EN 1304** reference norm and the test methods for the following characteristics:

- Impermeability
- Frost resistance
- Mechanical resistance

The conformity with the UNI EN 1304 standard is guaranteed by the CE marking.

Braas roof tiles are tested according to UNI EN 539/2 and pass the test after 400 freeze-thaw cycles (the norm requires 90 cycles for Italy and 150 cycles for the northern European countries). This performance ensures the durability even with harsh climate conditions.

## Installation Instructions

- The roof tiles must be installed on battens or proper support (min. batten size 40 x 40 mm)
- The roof tiles must be installed with straight bonds (aligned joints)
- The installation of roof tiles at a roof pitch < 30% is not possible
- Use of waterproofing underlay is always necessary (see below)

Roof pitch				Installation instructions		
Degrees %		Waterproofing layer	Batten Distance			
from	to	from	to			
	≥ 30,6°		≥ 60	A waterproofing underlay is always necessary to avoid	D. // 045.000	
24,1°	30,6°	45	60	leakages in case of ad- verse climate conditions. In	Batten gauge: 345-360 mm	
19,3°	24,1°	35	45	case of climates subject to Tropical conditions, the use	Recommended batten sec-	
16,7°	19,3°	30	35	of a waterproofing mem- brane is mandatory.	tion: 40 mm x 40 mm	
< 16,7°		< 30		not possible		

## Sequence of Installation







source: A.N.D.I.L



## Colour Range



Portoghese Flexa natural red



Portoghese Flexa antica





Portoghese Flexa dorotea

