

# METALROLL

METALROLL is a ventilating dry-fix solution for mechanically fixing ridge tiles. The system is a modern alternative to a mortar bedded ridge and creates a discreet finish that is far superior in aesthetics and function. Metalroll is made of highly resistant, high-performance materials and it is the most suitable ventilated ridge for the roofer's needs.

## BENEFITS

**Ventilation** – Breathable felt allows air to escape through the ridge preventing mould and rot of roof structure.

**Maintenance** – Maintenance-free allows expansion and contraction of roof in varying weather conditions.

**Waterproofing** - Water resistant and does not allow water to penetrate through the roofs surface.

**Time & labour-saving** - Easy to use; the no-fuss, no-mess application takes approximately 2.5 hours/10m roof ridge.

**Cost-saving** - No long-term maintenance required.

**Design aesthetics** - Neat and clean roof lines

## TECHNICAL DATA

Width	26 to 32 or 32 to 38 cm
Length	5 m/roll
Extensibility	50%
Ventilation	110 to 240 cm <sup>2</sup> /ml

## THE SYSTEM MECHANICS

- Installation requires a top batten on the ridge line to securely fix the ridge roll and ridge tiles.
- Seals ridge to ridge to give a tried and tested weather-tight seal.
- Provides an exceptionally durable method of securing ridge and hip tiles that ensures high resistance to storm damage.
- Gives a continuous weather-tight ventilation path from the interior roof cavity to the outside.



## Key Features



1. Reinforcement of nailing
2. Adjustable widths even with tiles with a higher profile
3. Ample protected ventilation area with solid felt
4. Unique CrepTec technology with a stretching ratio of 40% to 50%
5. Extremely robust material with good grip for fast installation
6. High adherence through butyl tested strip
7. Protection strip with silicone

### BMI ROOFING SYSTEMS SLU

Ctra. de Villaluenga a Cobeja, km. 3,500  
 45520 Villaluenga de la Sagra, Toledo, Spain  
[www.bmigroup.com/international](http://www.bmigroup.com/international)  
[technical.international@bmigroup.com](mailto:technical.international@bmigroup.com)