

RAPIDROLL

RAPIDROLL is a ventilating dry-fix solution for mechanically fixing ridge tiles. The system is a modern alternative to a mortar bedded ridge and creates a discreet finish that is far superior in aesthetics and function. Rapidroll is made of highly resistant, high-performance materials and it is the most suitable ventilated ridge for the roofer's needs.

BENEFITS

Ventilation – Breathable felt allows air to escape through the ridge preventing mould and rot of roof structure.

Maintenance – Maintenance-free allows expansion and contraction of roof in varying weather conditions.

Waterproofing - Water resistant and does not allow water to penetrate through the roofs surface.

Time & labour-saving - Easy to use; the no-fuss, no-mess application takes approximately 2.5 hours/10m roof ridge.

Cost-saving - No long-term maintenance required.

Design aesthetics - Neat and clean roof lines

TECHNICAL DATA


Width	37 to 39 cm
Length	5 m/roll
Extensibility	40%
Ventilation	130 cm ² /ml

THE SYSTEM MECHANICS

- Installation requires a top batten on the ridge line to securely fix the ridge roll and ridge tiles.
- Seals ridge to ridge to give a tried and tested weather-tight seal.
- Provides an exceptionally durable method of securing ridge and hip tiles that ensures high resistance to storm damage.
- Gives a continuous weather-tight ventilation path from the interior roof cavity to the outside.



Key Features



1. One canal of ventilation for optimal roof ventilation combined with protection against the intrusion of driving rain
2. Stretchable side strip & variable product width up to 39 cm
3. Robust full Alu-body ensuring high durability
4. Drain holes allow drain of condensed water or possibly collected rain / blowing snow out of the one-channel